

COMPRESSOR DATA SHEET
Rotary Compressor: Variable Frequency Drive

| MODEL DATA - FOR COMPRESSED AIR | | | |
|---------------------------------|---|--------------|--------------------------------|
| 1 | Manufacturer: Kaeser Compressors, Inc. | | |
| 2 | Model Number: SFC 75S - 175 psig / 460V/3ph/60Hz | Date: | 11/4/2011 |
| | <input type="checkbox"/> Air-cooled <input checked="" type="checkbox"/> Water-cooled | Type: | Screw |
| | <input checked="" type="checkbox"/> Oil-injected <input type="checkbox"/> Oil-free | # of Stages: | 1 |
| 3 | Rated Operating Pressure | 175 | psig ^b |
| 4 | Drive Motor Nominal Rating | 100 | hp |
| 5 | Drive Motor Nominal Efficiency | 94.1 | percent |
| 6 | Fan Motor Nominal Rating (if applicable) | 0.13 | hp |
| 7 | Fan Motor Nominal Efficiency | 60 | percent |
| 8* | Input Power (kW) | | Capacity (acfm) ^{a,d} |
| | 83.2 | Max | 374.7 |
| | 60.6 | | 287.5 |
| | 41.4 | | 191.8 |
| | 30.3 | | 132.8 |
| 9* | 19.0 | Min | 70.6 |
| | Total Package Input Power at Zero Flow ^{c,d} | | 0.0 |
| 10 | <p align="center">Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity</p> | | |

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator
 Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

- NOTES:
- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
 - The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
 - No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
 - Tolerance is specified in ISO 1217, Annex E, as shown in table below:
 NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



| Volume Flow Rate at specified conditions | | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|--|-----------------------|------------------|-----------------------------|---------------------------|
| m ³ / min | ft ³ / min | % | % | |
| Below 0.5 | Below 15 | +/- 7 | +/- 8 | +/- 10% |
| 0.5 to 1.5 | 15 to 50 | +/- 6 | +/- 7 | |
| 1.5 to 15 | 50 to 500 | +/- 5 | +/- 6 | |
| Above 15 | Above 500 | +/- 4 | +/- 5 | |

ROT 031