

COMPRESSOR DATA SHEET
Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: Kaeser Compressors, Inc.		
2	Model Number: SFC 90S - 160 psig / 460V/3ph/60Hz	Date: 11/4/2011	
	<input type="checkbox"/> Air-cooled <input checked="" type="checkbox"/> Water-cooled	Type: Screw	
	<input checked="" type="checkbox"/> Oil-injected <input type="checkbox"/> Oil-free	# of Stages: 1	
3	Rated Operating Pressure	160	psig ^b
4	Drive Motor Nominal Rating	100	hp
5	Drive Motor Nominal Efficiency	94.1	percent
6	Fan Motor Nominal Rating (if applicable)	0.13	hp
7	Fan Motor Nominal Efficiency	60	percent
8*	Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d
	93.8	Max	418.5
	76.2		353.9
	52.7		246.9
	38.4		174.1
9*	24.1	Min	98.2
	Total Package Input Power at Zero Flow ^{c,d}		0.0
10	<p align="center">Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity</p>		

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator
 Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

- NOTES:
- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
 - The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
 - No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
 - Tolerance is specified in ISO 1217, Annex E, as shown in table below:
 NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m^3/min	ft ³ /min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10%
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	

ROT 031