

KAESER
COMPRESSORS

Built for a lifetime.™



Rotary Screw Vacuum Packages

ASV, BSV, CSV

Capacities from 168 to 555 acfm

kaeser.com

ASV / BSV / CSV Series

Superior quality and efficient design

Kaeser's Rotary Screw Vacuum Packages feature a Sigma Profile™ airend specifically designed for vacuum applications such as dust collection, packaging, bottle and tube filling, drying, forming, and filtration. Their rugged design combines ease of use with exceptional reliability and simple maintenance.

Innovation you can trust

With a cutting edge research and development team committed to building industry-leading products, Kaeser continues to deliver better solutions to meet our customers' compressed air needs. Kaeser's expertise and world-wide reputation for superior reliability and efficiency offer great performance and peace of mind.

Kaeser reliability

Kaeser's vacuum screw compressors meet our rigorous "built for a lifetime" standard. Designed and built with Kaeser's generations of manufacturing experience, you can rest assured that these packages will continue to deliver the level of vacuum you need with the exceptional reliability you expect from a Kaeser vacuum screw package.

Service-friendly

From the ground up, these vacuum packages have been designed with the user in mind. Fewer wearing parts and using premium quality materials ensure reduced maintenance requirements, longer service intervals, and extended service life. A smart component layout with generously sized maintenance doors and removable panels simplify service and lower your operating costs.

Easy installation

Kaeser vacuum packages are completely pre-piped, pre-wired, and ready for installation. Packages feature a solid steel floor with anti-vibration mounts, eliminating the need for special foundations. A powder-coated, sound-dampening enclosure is standard on all models, ensuring low noise levels. These units also meet or exceed NFPA 99C guidelines for use in hospital installations.



Series features



Sigma Profile™ air end

The rotary screw vacuum air end with Sigma Profile has oversized bearings to ensure long service life. The pneumatic inlet valve is activated by a solenoid control valve and full-flow/idle switching is controlled by an adjustable vacuum switch. A full-flow positive displacement lubricant pump is driven by the female rotor for proper lubrication at all vacuum levels.

Belt drive with automatic tensioning

A multi v-belt drive efficiently transfers power from motor to air end. Our unique automatic tensioning device maintains proper tension to maximize energy efficiency, prolong belt life, and simplify routine maintenance. The belt tension can easily be verified through a window in the service panel.



Premium efficiency drive motor

Kaeser only uses Premium Efficiency Totally Enclosed Fan Cooled (TEFC) motors with class F insulation for extra protection from heat and contaminants. Remote grease fittings make maintenance a breeze. 230/460 or 575 V, 3-phase, 60 Hz is standard. Other voltages are available. Units come complete with a full-voltage magnetic starter and 115V-1 ph-60 Hz control voltage transformer.



Gas ballast system

This Kaeser exclusive feature prevents condensation from forming inside the vacuum pump, ensuring trouble-free operation.



Vacuum filter

On BSV and CSV packages, the externally mounted vacuum filter for the suction line is equipped with a pressure differential system to signal contamination and enable you to schedule needed maintenance.



Fluid separation system

Our multi-stage separation system provides low fluid carry-over (1-3 ppm), and extended filter service life. Our no-leak design features rigid steel piping, flexible connections, and vibration isolators. Each separator system includes wet side/dry side fittings to check differential pressure, an easy to read fluid level indicator, and our unique quick fluid drain system.



Air/coolant system

Kaeser's Rotary Screw Vacuum Package is equipped with an air-cooled fluid cooler. A package cooling fan is mounted on the motor drive shaft. The combination valve features a thermostatic element and full-flow micro fluid filter with spin-on replacement cartridge as one integrated unit.

The package has a combined reservoir and separator tank complete with safety relief valve and a multistage oversized separator cartridge. Two quick disconnect fittings make manual verification of differential pressure across the separator cartridge convenient. The package is shipped complete with an initial charge of synthetic fluid. Discharge can be easily piped away from unit due to an external connection on the package enclosure.



Intelligent control and protection

To protect your investment and ensure the most efficient operation possible, we control these packages with our Sigma Control 2™. This intelligent controller comes standard with multiple pre-programmed control profiles so you can select the one that best fits your application. Sigma Control 2 monitors more than 20 critical operating parameters, shuts the unit down to prevent damage, and signals if immediate service is required. It also tracks preventive maintenance intervals and provides notice when PMs are due. An RFID sensor provides secure access and simplifies managing maintenance intervals. An SD card slot with included SD card enables fast, easy software updates, storing key operational parameters, and offers long-term data storage for analyzing energy consumption and vacuum operation. Sigma Control 2 has superior communications capabilities. An Ethernet port and built-in web-server facilitate integration into the IIoT. ModBus, Profinet, Profibus, Devicenet, and other industrial communications interfaces are also available as plug in options for seamless integration into plant control/monitoring systems.

See our Sigma Control 2 brochure for more information.

Service-friendly design

The ASV, BSV, and CSV series rotary screw vacuum packages feature an open package layout. All of the major components are easily accessible, reducing preventive maintenance time by as much as 50% when compared to other similarly sized units.

For installations where space is limited, the front doors and the back access panels are easily removable, making it possible to perform maintenance from the front or back of the package.


Each door can also be removed for even more service accessibility options. The top panel fully extends, providing quick and easy access to the inlet filter, separator tank, and more.

When you consider the energy efficiency savings and the maintenance costs savings, it's clear that owning a *Built for a lifetime™* Kaeser rotary screw vacuum package will save you money, year after year.




Technical Specifications

Performance curves* ASV - BSV - CSV



*Data on the curves is based on 29.92" Hg absolute discharge pressure, inlet air temperature of 68°F, and 60 Hz electric motor operation.



Model	Capacity (acfm)	Max. Vacuum (%)	Rated Power (hp)	Power Supply	Overall Dimensions W x D x H (in.)	Standard Unit Connections (in.)		Dimensions (in.)		Weight (lb.)
						A	B	C	E	
ASV 40	168	99	10	230/460 V - 3 ph - 60 Hz	55 ⁷ / ₈ x 35 ¹ / ₄ x 42 ³ / ₄	2 ¹ / ₂ Flg.	1 ¹ / ₂ NPT	19 ¹ / ₈	11	1014
ASV 60	242		15							1036
BSV 80	296		20		63 ¹ / ₄ x 40 ³ / ₈ x 54 ³ / ₄	4 NPT	2 NPT	21 ¹ / ₄	13 ³ / ₄	1410
BSV 100	367		25							1587
CSV 125	463	99	30	230/460 V - 3 ph - 60 Hz	76 ³ / ₄ x 49 ¹ / ₂ x 57 ¹ / ₂	4 Flg.	3 NPT	28	14 ¹ / ₄	3031
CSV 150	555		40							3417

Specifications are subject to change without notice.

The world is our home

As one of the world's largest compressed air systems providers and compressor manufacturers, Kaeser Compressors is represented throughout the world by a comprehensive network of branches, subsidiary companies and factory trained partners.

With innovative products and services, Kaeser Compressors' experienced consultants and engineers help customers to enhance their competitive edge by working in close partnership to develop progressive system concepts that continuously push the boundaries of performance and compressed air efficiency. Every Kaeser customer benefits from the decades of knowledge and experience gained from hundreds of thousands of installations worldwide and over ten thousand formal compressed air system audits.

These advantages, coupled with Kaeser's worldwide service organization, ensure that our compressed air products and system deliver superior performance with maximum uptime.



**KAESER
COMPRESSORS**

Built for a lifetime.™

www.kaeser.com

Kaeser Compressors, Inc.
511 Sigma Drive
Fredericksburg, VA 22408 USA
Telephone: 540-898-5500
Toll Free: 800-777-7873
info.usa@kaeser.com

Kaeser Compressors Canada Inc.
3760 La Verendrye Street
Boisbriand, QC J7H 1R5 CANADA
Telephone: (450) 971-1414
Toll free: (800) 477-1416
info.canada@kaeser.com

**Kaeser Compresores de México
S de RL de CV**
Calle 2 #123
Parque Industrial Jurídica
76100 Querétaro, Qro.
Telephone: 01 (442) 218 64 48
sales.mexico@kaeser.com

**Kaeser Compresores de
Guatemala y Cia. Ltda.**
Calz. Atanasio Tzul 21-00, zona 12
El Cortijo II, Bodega 501
01012-Guatemala City
Telephone: +502 2412-6000
info.guatemala@kaeser.com